

531,657

Rec'd PCT/PTO 15 APR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/531657



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035351 A1


- (51) International Patent Classification⁷: B60R 1/06, 1/066, 1/072, 1/074
- (21) International Application Number: PCT/IB2003/005071
- (22) International Filing Date: 15 October 2003 (15.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/418,652 15 October 2002 (15.10.2002) US
- (71) Applicant (for all designated States except US): SCHEFENACKER VISION SYSTEMS FRANCE S.A. [FR/FR]; 154, avenue du Lys, B. P. 5, F-77191 Dammarie-les-Lys Cedex (FR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): DUMONT, Daniel [FR/FR]; 19 rue Rosa Bonheur, F-77250 Veneux les Sablons (FR).
- (74) Agents: ELLIS-JONES, Patrick, George, Armine et al.; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5JJ (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,

[Continued on next page]

(54) Title: REARVIEW MIRROR ASSEMBLY



(57) Abstract: The subject invention is a bracketless rearview mirror assembly (10) that is inexpensive and provides an easy assembly technique to attach the mirror assembly to a side of a motor vehicle (12). The mirror assembly includes a case (14) with a reflective mirror (16) and a guide mechanism (26). The motor vehicle (12) includes a mounting surface (48) with an opening (52) disposed between an inner side (48) and an outer side (50). A connector (42) is positioned between the case (14) and the inner side (48) of the mounting surface (46) of the vehicle. An adjustment mechanism (20) extends from inside the case, through the guide mechanism (26) and the connector (42), to the inner side (48) of the mounting surface (46). The adjustment mechanism (20) can be a simple handle (68) for manual adjustment or a harness (84) for encapsulating electronic controls for electrically adjusted mirrors. The mirror assembly (10) also allows the case (14) to move about the guide mechanism (26) and adjustment mechanism (20) to fold inward toward the vehicle (12).

WO 2004/035351 A1



CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

REARVIEW MIRROR ASSEMBLY

TECHNICAL FIELD

[0001] The present invention relates to a rearview mirror assembly with a bracketless mounting feature for attaching the mirror assembly to a side of a vehicle, and, more particularly, the present invention relates to a rearview mirror assembly with a mounting feature adaptable for various adjustment mechanisms.

5 BACKGROUND OF THE INVENTION

[0002] Traditional side rearview mirror assemblies are expensive and difficult to assembly in a mass-manufacturing environment. They require a mounting bracket that attaches a housing of the mirror assembly to a side of a motor vehicle. This bracket adds to the overall cost of the mirror assembly. Additionally, the design of
10 the bracket becomes specific to one particular vehicle since it is an exterior trim piece and must cooperate with the overall design scheme of the vehicle. Creating different brackets for different vehicles also adds to the cost of the mirror assembly.

[0003] In addition to the bracket having a specific design for aesthetic reasons, the bracket may also vary in its design to accommodate different mirror
15 adjustment mechanisms. Today, some vehicles use a manual adjustment mechanism with a simple handle extending from the mirror to the interior of the vehicle. Higher priced vehicles include electrically adjustable side rearview mirrors. These higher priced vehicles use additional components to adjust the mirror. Depending upon which adjustment mechanism is desired in the vehicle, a separate mounting bracket would be
20 necessary to accommodate the necessary components of each adjustment mechanism. Again, the need for different brackets adds to the cost of the vehicle.

[0004] Also, the use of a mounting bracket makes the assembly of the mirror to the vehicle difficult and time consuming. An assembly that would eliminate the use of a mounting bracket is highly desired.

25 [0005] There remains a need in the automotive industry for a side rearview mirror assembly that is inexpensive to manufacture, yet easy to assemble and able to

- 2 -

accommodate a variety of adjustment mechanisms. The present invention, as described below, fulfills each of these needs.

SUMMARY OF THE INVENTION

5 **[0006]** The subject invention is a mirror assembly having a mounting surface with an inner and outer side and an opening disposed therebetween. The mirror assembly also includes a case with a reflective mirror disposed with the case. Positioned within the case is a guide mechanism having a first aperture. A connector is positioned between the case and the inner side of the mounting surface and includes a
10 second aperture. Finally, the mirror assembly also includes an adjustment mechanism.

[0007] A further understanding of the present invention will be had in view of the description of the drawings and detailed description of the invention, when viewed in conjunction with the subjoined claims.

15 BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Other advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

20 **[0009]** Figure 1 is a perspective view of a motor vehicle with a mirror assembly of the subject invention;

[0010] Figure 2 is an exploded view of the mirror assembly with a handle adjustment mechanism for manual adjustment of a mirror;

[0011] Figure 3 is an exploded view of the mirror assembly with a harness
25 adjustment mechanism for electrical adjustment of the mirror;

[0012] Figure 4A is an outer perspective view of a connector of the mirror assembly;

[0013] Figure 4B is an inner perspective view of the connector of the mirror assembly;

30 **[0014]** Figure 5 is a perspective view of an inner side of a mounting surface of the motor vehicle;

- 3 -

[0015] Figure 6 is a perspective view of a guide mechanism of the mirror assembly of the subject invention;

[0016] Figure 7 is a perspective view of the handle adjustment mechanism of the mirror assembly;

5 [0017] Figure 8 is an inner perspective view of the handle adjustment mechanism extending through the connector and into the inner side of the mounting surface of the motor vehicle;

[0018] Figure 9 is a perspective view of the mirror assembly of the subject invention having a handle adjustment mechanism;

10 [0019] Figure 10 is a perspective view of the mirror assembly of the subject invention having the harness adjustment mechanism;

[0020] Figure 11 is a perspective view of the mirror assembly of the subject invention having the harness adjustment mechanism and the case moveable; and

15 [0021] Figure 12 is a perspective view of the case of the mirror assembly.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0022] Referring to the Figures, wherein like numerals indicate like or corresponding parts throughout the several views, a mirror assembly is generally shown at 10 in FIG. 1. The mirror assembly 10 is shown attached to the side of a motor vehicle generally shown at 12. The subject invention includes a mirror assembly 10 having three distinct embodiments – a handle mirror assembly 10, an electrically actuated mirror assembly 10 and a moving case mirror assembly 10. All three embodiments have the components described herein and shown in Figures 2 and 3.

25 [0023] The mirror assembly includes a case 14 having a generally rectangular shape and a reflective mirror 16 disposed within said case 14. The shape of the reflective mirror 16 and case 14 of the present invention, however, can be of any shape. The reflective mirror 16 includes a back plate 18 that is connected to an adjustment mechanism 20. The adjustment mechanism 20 has a first end 22 and a
30 second end 24. The first end 22 of the adjustment mechanism 20 is attached to the

- 4 -

back plate 18 of the reflective mirror 16 by conventional means commonly used in the art.

[0024] The case 14 also includes a guide mechanism 26. The guide mechanism 26 has a first aperture 28. With the first end 22 of the adjustment mechanism 20 connected to the back plate 18 of the reflective mirror 16, the second end 24 extends through this first aperture 28 of the guide mechanism 26 to an outer side of the case 14. The guide mechanism 26 also includes wings 30 extending from each side of the first aperture 28. An inner side 32 of the guide mechanism 26 faces the reflective mirror 16 while an outer side 34 faces the motor vehicle. The outer side 34 of the guide mechanism 26 includes a rib 36 and a knob 38. The rib 36 is used to fixedly position the guide mechanism 26 to the case 14 in the handle mirror assembly 10 and electrically actuated mirror assembly 10. The case 14 receives the rib 36 in a slot (not shown) to fixedly position the guide mechanism 26 in the case 14. The knob 38 is used in the third embodiment of the moving case mirror assembly 10. The case 14 in the moving case embodiment includes a plurality of grooves 40. These grooves 40 receive the knob 38 of the guide mechanism 26 as the case 14 rotates about the guide mechanism 26 and the adjustment mechanism 20. Rotating the case 14 permits the mirror assembly 10 to be folded inward against the exterior side of the vehicle 12. Folding the mirror assembly 10 inward reduces the overall width of the vehicle thereby assisting when shipping the vehicle 12 or parking the vehicle 12 in confined spaces.

[0025] In order to attach the case 14 of the mirror assembly 10 to the vehicle 12 a connector 42 is positioned between the case 14 and the vehicle 12. The connector 30 contains a second aperture 44 that also receives the second end 24 of the adjustment mechanism 20. The motor vehicle 12 includes a mounting surface 46 having an inner side 48 and an outer side 50. The mounting surface 46 is positioned on the side of the vehicle 12. The mounting surface 46 includes an opening 52. This opening 52 receives the connector 42 and the second end 24 of the adjustment mechanism 20. The connector 42 also includes a threaded hole 54 for receiving a screw 56. The screw 56 is positioned at the inner side 48 of the mounting surface 46 and threadably engages the threaded hole 54 to fixedly attach the connector 42 to the vehicle 12. To further secure the connector 42 to the vehicle 12, the connector 42

- 5 -

includes at least one locking knob 58 that engages an extension 60 in the mounting surface 46. The preferred embodiment illustrates the use of two locking knobs 58 that engage two extensions 60 in the mounting surface 46, however, only one locking knob 58 is required. The locking knob 58 requires that the connector 42 be properly oriented for insertion through the opening 52 of the mounting surface 46. Once inserted through the opening 52, the connector 42 is rotated and then secured to the vehicle 12. In addition to the screw 56, the connector 42 also includes a lip 62 having a locking boss 64. The locking boss 64 is received in a locking embossment 66 on the outer side 50 of the mounting surface 46. Therefore, to properly connect the mirror assembly 10 to the vehicle 12, the connector 42 is orientated to be inserted through the opening 52 of the mounting surface 46 by passing the locking knob 58 through the extension 60 in the mounting surface 46. Once properly inserted, the connector 42 is rotated and the locking boss 64 is received in the locking embossment 66. The lip 62 is positioned flat against the outer side 50 of the mounting surface 46. Finally, the screw 58 is threadably engaged with the threaded hole 54 of the connector 42.

[0026] The adjustment mechanism 20 in all three embodiments extends through the first aperture 28 of the guide mechanism 26, the second aperture 44 of the connector 42 and the opening 52 in the mounting surface 46. Accordingly, the second end 24 of the adjustment mechanism 20 is positioned on the inner side 48 of the mounting surface 46 and thereby inside the vehicle 12 and accessible to an operator.

[0027] In the first embodiment, the handle mirror assembly 10, the adjustment mechanism 20 is a handle 68. The handle 68 has a generally tubular shape with an angled extension 70 at the second end 24. The angled extension 70 begins when the handle 68 reaches the inner side 48 of the mounting surface 46. The extension 70 angles toward the operator of the vehicle 12 for manual adjustment of the reflective surface 18. The handle 68 also includes a locking mechanism 72 positioned at the inner side 48 of the mounting surface 46. The locking mechanism 72 is used to limit the vertical adjustment of the reflective surface 18. The locking mechanism 72 is shown as a rectangular extension on the handle 68. The locking mechanism 72 interferes with the connector 42 when moved to maximum upper or lower positions. The interference prevents any further vertical adjustment of the reflective surface 18.

- 6 -

The width of the second aperture 44 of the connector 42 limits the horizontal adjustment of the reflective surface 18 in the case 14. The horizontal stroke of the handle 68 is limited when the handle 68 contacts a side surface of the second aperture 44 of the connector 42. To position the handle 68 within the case 14 the adjustment mechanism 20 includes a lip 74. Positioned between the lip 74 and the inner side 32 of the guide mechanism 26 is a biasing device 76. The biasing device 76, most commonly a spring, urges the guide mechanism 26 against the case 14 and the locking mechanism 72 of the handle 68 against the connector 42, thereby properly positioning the components of the mirror assembly 10. Furthermore, the portion of the handle 68 positioned in the first aperture 28 of the guide mechanism 26 has a flattened surface 78 on one side of the tubular handle 68. This flattened surface 78 mates against a plane 80 within the first aperture 28 of the guide mechanism 26. The mating of the flattened surface 78 and the plane 80 prevents rotation of the handle 68 within the mirror assembly 10. Again, this ensures that the components of the mirror assembly 10 are properly positioned.

[0028] In the second embodiment, the electrically actuated mirror assembly 10, the adjustment mechanism 20 includes an electric motor 82 and a harness 84. The electric motor 82 is positioned within the case 14 and is connected to the back plate 18 of the reflective mirror 16. The electric motor 82 actuates movement of the back plate 18 and reflective mirror 16 within the case 14. The electric motor 82 receives power and control signals through electrical controls 86. The electrical controls 86 are connected to the electric motor 82 and extend to inside the vehicle 12. The controls 86 are contained within the harness 86. The harness 84 encapsulates the electronic controls 86 and extends from the electric motor 82 to the inside of the vehicle 12. The harness 84, typically made of plastic, also includes a plurality of strengthening ribs. Similarly configured like the handle 68, the harness 82 also includes a lip 74 and a flattened surface 78. A biasing device 76 is positioned between the lip 74 and the inner side 32 of the guide mechanism 26. As with the handle 68, the flattened surface 78 mates against the plane 80 in the first aperture 28 of the guide mechanism 26 to prevent rotation. The electronic controls 86 extend through the harness 84 and into the vehicle 12. The vehicle 12 will include a control mechanism (not shown) in which the

- 7 -

operator commands movement of the reflective mirror 16 within the case 14 and a signal is sent through the electrical controls 86 and received by the electric motor 82.

[0029] The final embodiment, the moving case mirror assembly 10, only uses the adjustment mechanism 20 to properly position the components of the mirror assembly 10. This embodiment only includes the harness 84. The harness 84 is positioned as in the electrically actuated mirror assembly 10. The biasing device 76 is positioned between the lip 74 and the inner side 32 of the guide mechanism 26 to properly position the components of the assembly 10. The harness 84 is left hollow. A plug (not shown) conceals the second end 24 of the harness 84 positioned inside the vehicle 12. The plug is strictly provided for aesthetic purposes. The mirror assembly 10 is adjusted by moving the case 14 about the guide mechanism 26. The knob 38 positioned on the outer side 34 of the guide mechanism 26 is received in one of a plurality of grooves 40 in the case 14. The operator manually adjusts the mirror assembly 10. There are no control mechanisms or handles. At a maximum position, the mirror assembly 10 is flat against the side of the vehicle 12.

[0030] All three embodiments utilize the same components, thereby reducing the manufacturing costs for producing the vehicle 12. All assemblies 10 use the same case 14, guide mechanism 26 and connector 42. The only component that varies is the type of adjustment mechanism 20 – either the handle 68, electric motor 82 with harness 84 or the harness 84 alone. The simplicity of alternating the adjustment mechanism 20 to accommodate various options with each vehicle 12 reduces the overall production costs and assembly efforts.

[0031] Those skilled in the art can now appreciate from the foregoing description that the broad teachings of the present invention can be implemented in a variety of forms. Therefore, while this invention has been described in connection with particular examples thereof, the true scope of the invention should not be so limited, since other modifications will become apparent to the skilled practitioner upon a study of the drawings, specification and following claims.

- 8 -

CLAIMS

What is claimed is:

1. A mirror assembly comprising:
 - a mounting surface having an inner side and an outer side and an opening disposed therebetween;
 - a case;
 - 5 a reflective mirror disposed within said case;
 - an adjustment mechanism;
 - a guide mechanism positioned within said case and having a first aperture; and
 - a connector having a second aperture and disposed between said case and said inner side of said mounting surface.
2. A mirror assembly as described in claim 1 wherein said adjustment mechanism includes a first end connected to said reflective mirror and a second end extending through said first aperture of said guide mechanism, said second aperture of said connector and said opening of said mounting surface.
3. A mirror assembly as described in claim 2 wherein said adjustment mechanism is a handle for manual adjustment of said reflective mirror within said case.
4. A mirror assembly as described in claim 3 wherein said guide mechanism includes a rib for fixedly positioning said guide mechanism within said case.
5. A mirror assembly as described in claim 3 wherein said handle includes a locking mechanism for limiting vertical adjustment of said reflective mirror.
6. A mirror assembly as described in claim 2 wherein said adjustment mechanism is an electric motor and a harness encapsulating electrical controls for adjustment of said reflective mirror within said case.

- 9 -

7. A mirror assembly as described in claim 6 wherein said guide mechanism includes a rib for fixedly positioning said guide mechanism within said case.

8. A mirror assembly as described in claim 2 wherein said case is moveable about said adjustment mechanism and said guide mechanism.

9. A mirror assembly as described in claim 8 wherein said case includes a plurality of grooves for receiving a knob of said guide mechanism

10. A mirror assembly as described in claim 2 wherein said adjustment mechanism includes a biasing device for maintaining said adjustment mechanism and said guide mechanism properly positioned within said case.

11. A mirror assembly as described in claim 2 wherein said connector has an inner end and an outer end.

12. A mirror assembly as described in claim 11 wherein said connector further includes a lip having a locking boss at said outer end.

13. A mirror assembly as described in claim 12 wherein said mounting surface has a locking embossment on said outer side for receiving said locking boss of said connector.

14. A mirror assembly as described in claim 13 wherein said mounting surface further includes a screw at said inner side for attaching said connector to said mounting surface.

15. A mirror assembly as described in claim 14 wherein said inner end of said connector includes at least one locking knob

- 10 -

16. A mirror assembly as described in claim 15 wherein said inner end of said connector further includes a threaded hole for receiving said screw of said mounting surface.

17. A mirror assembly as described in claim 16 wherein said opening of said mounting surface includes at least one extension for receiving said locking knob.

18. A mirror assembly as described in claim 2 wherein said first aperture of said guide mechanism includes a plane to prevent rotation of said adjustment mechanism while in said first aperture.

19. A mirror assembly for use as a side rearview mirror on a motor vehicle comprising:

- a mounting surface integral with said motor vehicle having an inner side and an outer side and an opening disposed therebetween;

- a case having a reflective mirror disposed therein;

- a guide mechanism having a first aperture and positioned within said case;

- a connector having a second aperture and disposed between said case and said inner side of said mounting surface; and

- an adjustment mechanism for changing the position of the reflective mirror having a first end connected to said reflective mirror and a second end extending through said first aperture of said guide mechanism, said second aperture of said connector and said opening of said mounting surface.

20. A mirror assembly as described in claim 19 wherein said adjustment mechanism is a handle for manual adjustment of said reflective mirror within said case.

21. A mirror assembly as described in claim 20 wherein said handle includes a locking mechanism for limiting vertical adjustment of said reflective mirror.

- 11 -

22. A mirror assembly as described in claim 20 wherein said guide mechanism includes a rib for fixedly positioning said guide mechanism to said case.

23. A mirror assembly as described in claim 19 wherein said adjustment mechanism is an electric motor and a harness encapsulating electronic controls for controlling adjustment of said reflective mirror in said case.

24. A mirror assembly as described in claim 23 wherein said guide mechanism includes a rib for fixedly positioning said guide mechanism to said case.

25. A mirror assembly as described in claim 19 wherein said case is moveable around said adjustment mechanism and said guide mechanism.

26. A mirror assembly as described in claim 25 wherein said case includes a plurality of grooves for receiving a knob on said guide mechanism.

27. A mirror assembly as described in claim 19 wherein said adjustment mechanism further includes a biasing device for properly positioning said adjustment mechanism and said guide mechanism within said case.

28. A mirror assembly as described in claim 19 wherein said connector includes an inner end and an outer end, said inner end including a threaded hole and at least one knob and said outer end including a lip with a locking boss.

29. A mirror assembly as described in claim 28 wherein said inner side of said mounting surface includes a screw for penetrating said threaded hole of said connector and attaching said connector to said mounting surface.

30. A mirror assembly as described in claim 29 wherein said outer side of said mounting surface includes a locking embossment to receive said locking boss of said connector.

31. A mirror assembly as described in claim 30 wherein said opening of said mounting surface includes at least one extension for receiving said knob of said connector.

32. A mirror assembly as described in claim 19 wherein said first aperture of said guide mechanism includes a plane for preventing rotation of said adjustment mechanism within said first aperture.

33. A mirror assembly for use on a motor vehicle comprising:
a mounting surface having an inner side and an outer side and an opening disposed therebetween;
a case;
a reflective mirror disposed within said case;
a guide mechanism fixedly positioned within said case and having a first aperture with a plane;
a connector having a second aperture and positioned between said case and said inner side of said mounting surface; and
a handle having a first end connected to said reflective mirror and a second end extending through said first aperture of said guide mechanism, said second aperture of said connector and said opening of said mounting surface.

34. A mirror assembly as described in claim 33 wherein said handle includes a locking mechanism for limiting vertical movement of said reflective mirror.

35. A mirror assembly as described in claim 33 wherein said handle further includes an angled extension at said second end.

36. A mirror assembly as described in claim 33 wherein said first end of said handle includes a lip and a flat surface for mating with said plane of said guide mechanism.

- 13 -

37. A mirror assembly as described in claim 33 including a biasing device for properly positioning said guide mechanism and said handle within said case.

38. A mirror assembly for use on a motor vehicle comprising:
a mounting surface having an inner side and an outer side and an opening disposed therebetween;
a case;
a reflective mirror disposed within said case;
a guide mechanism fixedly positioned within said case and having a first aperture with a plane;
a connector having a second aperture and positioned between said case and said inner side of said mounting surface; and
a harness having a first end connected to said reflective mirror and a second end extending through said first aperture of said guide mechanism, said second aperture of said connector and said opening of said mounting surface.

39. A mirror assembly as described in claim 38 including an electric motor disposed in said case for actuating movement of said reflective mirror via an electronic control mechanism positioned inside the motor vehicle.

40. A mirror assembly as described in claim 38 wherein said harness is molded from plastic and includes a plurality of strengthening ribs.

41. A mirror assembly as described in claim 38 including a biasing device for properly positioning said guide mechanism and said harness within said case.

42. A mirror assembly for use on a motor vehicle comprising:
a mounting surface having an inner side and an outer side and an opening disposed therebetween;
a case;

- 14 -

a reflective mirror disposed within said case;


a guide mechanism positioned within said case and having a knob and a first aperture with a plane;

a connector having a second aperture and positioned between said case and said inner side of said mounting surface;

a harness having a first end connected to said reflective mirror and a second end extending through said first aperture of said guide mechanism, said second aperture of said connector and said opening of said mounting surface; and

said case including a plurality of grooves for receiving said knob of said guide mechanism, wherein said case is moveable about said adjustment mechanism and said guide mechanism.

Figure - 1






Figure - 2




Figure - 3




Figure - 4A




Figure - 4B




Figure - 5






Figure - 6






Figure - 9




Figure - 10




Figure - 11




Figure - 12

INTERNATIONAL SEARCH REPORT

International Application No
B 03/05071

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60R1/06 B60R1/066 B60R1/072 B60R1/074

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 4 636 045 A (SUZUKI MASARU) 13 January 1987 (1987-01-13) column 2, line 43 -column 4, line 38; figures 1,2	1-3,11, 18-20,33 5,8,10, 21,25, 27-29
A	WO 96 23676 A (ROVER GROUP ;BLOOMFIELD MICHAEL (GB)) 8 August 1996 (1996-08-08) abstract; figure 1	1,19,33, 38,42
A	US 2002/145816 A1 (NICKEL VOLKER ET AL) 10 October 2002 (2002-10-10) figure 3	1
A	WO 02 076791 A (GILBERT ROBERT ;SCHEFENACKER VISION SYSTEMS AU (AU); SCHUURMANS MA) 3 October 2002 (2002-10-03) abstract; figure 7	38,39,42
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

18 March 2004

Date of mailing of the international search report

29/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Petersson, M

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/GB 03/05071

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 1 038 730 A (BRITAX WINGARD LTD) 27 September 2000 (2000-09-27) abstract; figure 2</p>	38, 39, 42

INTERNATIONAL SEARCH REPORT
Information on patent family members

International Application No
PCT/JP 03/05071

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4636045	A	13-01-1987	JP 1653363 C	30-03-1992
			JP 3010538 B	13-02-1991
			JP 60053443 A	27-03-1985
			JP 60095344 U	28-06-1985
			DE 3432183 A1	21-03-1985
			GB 2146302 A , B	17-04-1985
WO 9623676	A	08-08-1996	WO 9623676 A1	08-08-1996
			GB 2311267 A , B	24-09-1997
US 2002145816	A1	10-10-2002	DE 10103402 A1	14-08-2002
			FR 2820096 A1	02-08-2002
			JP 2002283918 A	03-10-2002
WO 02076791	A	03-10-2002	WO 02076791 A1	03-10-2002
			EP 1373020 A1	02-01-2004
EP 1038730	A	27-09-2000	DE 60003248 D1	17-07-2003
			EP 1038730 A2	27-09-2000
			JP 2000280824 A	10-10-2000
			US 2002075578 A1	20-06-2002
			US 6371619 B1	16-04-2002